

Model	Motor	Dimensions mm						Input Power (W)	Input Current (A)	RPM	Flow rate (m³/h)	Static pressure (ΔPa)	Curve n°
		A	B	C	D	E	F						
FF65 - 180/30	30-1	30	68,7	182	265	200	191	41	0,31	2050	190	75	1
FF65 - 180/40	40-1	40	78,7	182	275	200	191	50	0,40	2400	225	85	2
FF65 - 240/30	30-1	30	68,7	242	325	260	251	42	0,32	1400	175	80	3
FF65 - 240/35	35-1	35	73,7	242	330	260	251	51	0,39	1850	230	85	4
FF65 - 240/40	40-1	40	78,7	242	335	260	251	52	0,41	2100	260	90	5
FF65 - 270/35	35-1	35	73,7	272	360	290	281	53	0,41	1500	220	83	6
FF65 - 270/40	40-1	40	78,7	272	365	290	281	55	0,43	1600	250	85	7
FF65 - 300/30	30-1	30	68,7	302	385	320	311	43	0,33	1240	200	70	8
FF65 - 300/40	40-1	40	78,7	302	395	320	311	56	0,44	1500	300	85	9
FF65 - 360/30	30-1	30	68,7	362	445	380	371	44	0,33	1050	225	65	10
FF65 - 360/40	40-1	40	78,7	362	455	380	371	56	0,44	1300	265	75	11