

Model	Motor	Dimensions mm				Input Power (W)	Input Current (A)	RPM	Flow rate (m³/h)	Static pressure (ΔPa)	Curve n°
		A	B	C	D						
TF 90/15	15-1	15	51,2	94	157	16	0,13	2250	80	53	1
TF 90/20	20-1	20	56,2	94	162	20	0,15	2550	92	59	2
TF 120/15	15-1	15	51,2	124	187	18	0,14	1800	101	49	3
TF 120/20	20-1	20	56,2	124	192	22	0,16	2250	127	60	4
TF 180/15	15-1	15	51,2	184	247	19	0,15	1250	107	48	5
TF 180/20	20-1	20	56,2	184	252	23	0,17	1700	144	62	6
TF 180/30	30-1	30	66,2	184	262	35	0,25	2450	212	73	7
TF 180/35	35-1	35	71,2	184	267	41	0,31	2550	234	75	8
TF 240/20	20-1	20	56,2	244	312	24	0,18	1200	149	55	9
TF 240/30	30-1	30	66,2	244	322	37	0,27	2200	262	78	10
TF 240/35	35-1	35	71,2	244	327	45	0,33	2350	283	80	11
TF 270/20	20-1	20	56,2	274	342	24	0,18	1150	163	42	12
TF 270/30	30-1	30	66,2	274	352	39	0,28	1950	280	78	13
TF 270/35	35-1	35	71,2	274	357	46	0,34	2150	313	80	14
TF 300/20	20-1	20	56,2	304	372	24	0,18	1150	171	45	15
TF 300/30	30-1	30	66,2	304	382	40	0,29	1750	268	77	16
TF 300/40	40-1	40	76,2	304	392	48	0,37	2400	348	80	17
TF 360/20	20-1	20	56,2	364	432	24	0,18	950	183	40	18
TF 360/30	30-1	30	66,2	364	442	40	0,30	1350	262	78	19
TF 360/40	40-1	40	76,2	364	452	53	0,40	1900	325	78	20
TF 420/30	30-1	30	66,2	424	502	41	0,31	1200	271	70	21
TF 420/40	40-1	40	76,2	424	512	54	0,42	1600	359	76	22
TF 480/30	30-1	30	66,2	484	562	40	0,30	1150	283	62	23
TF 480/40	40-1	40	76,2	484	572	54	0,42	1250	364	69	24